



# SPIRAL<sup>®</sup> LH<sup>®</sup>

## HIGH PERFORMANCE LOW HEADROOM ROLLING DOOR



Shown with optional vision slats

# SPIRAL<sup>®</sup> LH<sup>®</sup>

## High Security and High Speed, Designed for Low Headroom Applications

With an opening speed of up to 60 inches per second, the Spiral LH door (Low Headroom) offers the speed needed for high-traffic situations while meeting the low headroom requirements of parking garages and other commercial structures. Rigid, aluminum slat construction eliminates any need for a second overnight security door and the rubber weatherseal provides a tight seal.

Crisp lines give the Spiral LH door a stylish look that's great for parking and other commercial, institutional and residential applications. Because its anodized aluminum slats will not corrode, you can count on its look to last for many years even under the worst weather conditions.



Shown with optional vision slats



### Solid Security

- Minimum 1 3/16-inch thick double walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system

### Low Headroom

- The low lintel design requires only 10 inches of headroom clearance

### Ultra Quiet

- High performance technology and low headroom angled track offer a quiet and unobtrusive operation

### Unparalleled Performance

- Variable speed AC drive system - with soft acceleration and deceleration - smooths out routine stops and starts

### Energy Efficient & Tight Seal

- Aluminum slats and durable rubber membrane provides a 100% seal against dust, drafts and inclement weather

### Smooth Operation

- Advanced System 4<sup>®</sup> door controller enables precise door positioning, speed adjustment and control of all door functions

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

# SPIRAL® LH®

## HIGH PERFORMANCE LOW HEADROOM ROLLING DOOR



Automotive  
Dealership



Parking



Government &  
Municipalities



Security

### Size/Dimensions


- Maximum width up to 20'
- Maximum height up to 16'4"

### Travel Speed

- Opening speed up to 60 inches per second

### Unique Track Design

- Special track design allows door to fit in low headroom areas with as little as 10 inches of clearance above the door opening
- Compact, variable speed motor with soft acceleration and deceleration and braking for smooth starts and stops



Variable speed motor

### Architectural Styling

- Sleek double-walled aluminum slats are 6 inches high with an integral weatherseal between each panel
- Durable 'Rytec silver' powder coated finish is UV-stable and resists rust, corrosion and fingerprints



Sleek six inch high slats shown

### Electrical Controls

- System 4® controller housed in a NEMA 4x rated enclosure with factory set parameters
- Intelligent processor monitors and controls power consumption
- Advanced self-diagnostics for troubleshooting



System 4 shown with optional rotary disconnect

Standard maximum sizes shown; larger sizes may be available upon request.

### Panel Design

- Integral rubber weatherseal between the slats provides a tight weatherseal across the entire panel
- Patented hinge design allows for removal and replacement of single slat without disassembling the door panel



Integral rubber weatherseal

### Safety

- Standard Advanced<sup>3</sup> Light Curtain Safety System
- Standard Pathwatch® Safety Light System
- Standard electric reversing edge
- Standard Ry-Wi® Wireless System
- Standard mechanical brake release lever allows door opening in the event of power failure



Pathwatch warning lights and brake release lever

### Warranty

- Five-year limited warranty on materials and components
- Two-year limited warranty on electrical components



### Options

- Insulated, ventilated or vision slats
- Dual thru-beam photo eyes
- Powder coated finish available in RAL classic colors or custom match
- Motion, presence, loop or radio controlled door activators



Solid and vision slats shown

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change  
© 2018 Rytec Corporation LIT020818

**RytecDoors.com**  
**888-GO-RYTEC**

info@rytecdoors.com  
P: 262.677.9046 F: 262.677.2058  
One Cedar Parkway, PO Box 403  
Jackson, WI 53037-0403

**RYTEC**  
HIGH PERFORMANCE DOORS