Cleaning by Colors™





New Generation® Spin Bonnet Solution



For interim, non-residual bonnet cleaning of wools and stain resistant carpets. Lifts soil from fiber tips.

1 Gallon (128 oz./3.8 L) Reorder: SBNG-640

- Interim carpet maintenance
- · Use on Wool, Stain Resistant Fibers
- Biodegradable
- Concentrated

For Industrial and Institutional Use Only.

Always vacuum thoroughly and test fibers for colorfastness before using.

Don't forget to treat problem stains as soon as possible for best results.

Spin Bonnet Solution

Directions Dilutions:

Carpet

Always vacuum thoroughly and test fiber for color- **pH:** 7-7.5/Neutral fastness before using.

Dilute 12 ounces of New Generation® Spin Bonnet Solution to 1 gallon of water (1:10 dilution). One diluted gallon covers approximately 1,000 sf.

Using a clean corrosion-resistant sprayer, lightly spray surface of bonnet for lubrication and a 10' x 10' (100 sf) section of the carpet to be cleaned. Agitate with carpet comb and allow 10 minutes dwell time.

Buff carpet in an elliptical patter. When bonnet becomes soiled, use reverse side. Keep several clean, dry bonnets on hand. Soiled pads can be laundered and reused.

Groom with carpet comb and allow to thoroughly dry before use.

For Industrial an Institutional Use Only.

First Aid:

For skin contact, wash with soap and water. For eye contact, remove contact lenses and flush with large quantities of cool, running water for at least 15 minutes. If Eye or Skin irritation develops and/ or persists, seek medical attention. Do not take internally. If ingested, drink large quantities of water, seek medical attention. If inhaled: remove to fresh air, seek medical attention

Ingredients: Water, 2-Propanol-1-Butoxy, 1-Methoxy-2-Propanol, 1-(2-Methoxy-1-Methylethoxy)-2-Propanol.

Health: 1 Fire: 2

Reactivity: 0 Special: 0

Fragrance: Fresh & Clean

Caution: Keep out of reach of children and pets. Harmful if swallowed. Carpets & Rugs become slippery when wet. Use care when descending stairs or walking from carpet to hard surfaces.

Protect from freezing. Store in a cool, dry area, below 120 degrees F.

RECYCLE! Before disposing, check with local, state and federal regulations for compliance.

Questions?

Contact Core Products Co., Inc. 401 Industrial Rd., Canton, TX 75103 800.825.2673 or www.coreproductsco.com

