## **SPECIFICATIONS**

**Enclosed Car Trailer** 

## The ULTIMATE Carrying Case For Your Car (888) 5-JIMGLO www.JIMGLO.com

Lengths							Weights	
	Slope/Square Front		32" V-Nose Front			9,999 lb GVWR	12,000 lb GVWR	
Size	Interior Length	Overall Length	Interior Side Wall	Interior at Apex	Overall Length	Trailer Weight	Trailer Weight	
18'	18'	23'	18'	20' 8"	23'	2,600 lbs	2,900 lbs	
20'	20'	25'	20'	22' 8"	25'	2,700 lbs	3,000 lbs	
22'	22'	27'	22'	24' 8"	27'	2,800 lbs	3,100 lbs	
24'	24'	29'	24'	26' 8"	29'	2,900 lbs	3,200 lbs	
26'	26'	31'	26'	28' 8"	31'	NA	3,300 lbs	

Heights							
Interior Height	Overall Height	Rear Ramp Door Opening	Driver Side Door Opening				
			(width X height)				
6'0"   72"	96"	74"	120" X 60"				
6'6"   78"	102"	80"	120" X 66"				
7'0"   84"	108"	86"	120" X 66" *				
7'6"   90"	114"	92"	120" X 66" *				
8'0"   96"	120"	98"	120" X 66" *				
8'6"   102"	126"	104"	120" X 66" *				
9'0"   108"	132"	110"	120" X 66" *				

<sup>\*</sup> Additional Height Available

GVWR		9,999 lbs	12,000 lbs		
Axles		(2) 5,200 lb Torsion	(2) 6,000 lb Torsion		
Brakes		4 Wheel Electric			
Coupler		2 5/16	2 5/16" Ball		
Height	Loading	18 1/2"	19"		
	Bed to Top of Fender	10 1/2"	11 1/2"		
	Bed to Top of Tire	6 1/2"	7 1/2"		
	Top of Ball	20"	21"		
Fenders	Driver Side Removable - Aluminum				
Frame		2" X 6" X 1/4" Tubular Aluminum			
Plug		7 Pin RV Plug			
Tie-Downs		V-Track w/ 4 Clips (4' Front and 4' Rear on Each Sic			
Tires	Size	ST225/75R15 Radial	235/80R16 Radial		
	Load Range	Load Range D	Load Range E		
	Ply Rating	8 Ply	10 Ply		
Wheels		Aluminum 6 Lug	Aluminum 8 Lug		
Width	Overall	102"			
	Interior	96	96"		
	Rear Door Opening	94"			
Rear	Door (between springs)	87"			
Between Fenders		83"			

