

WIRELESS - a LUCIO everywhere

Custom Wireless Audio Products

XStream™ X5



superior content

Cloud

Popular Services

Wired/Wireless

NAS Content



better performance

All Digital

High-Performance Amp

Lossless Synchronization

Premium Audio Connectors



real control

3rd Party Control

IR

Keypads

Apps

The first wireless system with audiophile sound and whole-house flexibility





Russound X5 wireless streamer / controller / amplifier









Made for iPhone iPad



AirPlay works with iPhone, iPad, and iPod touch with iOS 4.3.3 or later, Mac with OS X Mountain Lion, and Mac and PC with iTunes 10.2.2 or later.





Expand your options



X1-RX220

Wireless Receiver Amplifier

X1-RX2

Wireless Receiver







wireless control via smartphone or tablet, using My Russound app











^{*}Services provided by DMS-3.1 and C-Series Controller.



Acclaim[™] Thin Bezel Speakers with magnetic grilles









Model	Description	Woofer	Tweeter	Recommended Power	Frequency Response	Sensitivity	Nominal Impedance	Overall Dimensions	Cut-out Dimensions	Mounting Depth
Angled models										
RSA-61 (each)	15° angled two-way in-ceiling	6.5" (16.51 cm) polypropylene cone	1" (2.54 cm) Pivoting PEI	5 - 80 watts	50Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	4.28" (10.87 cm)
RSA-62 (each)	15° angled two-way in-celling	6.5" (16.51 cm) IMPP ribbed cone	1" (2.54 cm) Pivoting silk	5 - 100 watts	45Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	4.4" (11.18 cm)
RSA-63 (each)	15° angled two-way in-ceiling	6.5" (16.51 cm) Kevlar cone	1" (2.54 cm) Pivoting Teteron	5 - 120 watts	40Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" día. (23.19 cm)	8.375" dia. (21.27 cm)	4.56" (11.58 cm)
Flat models										
RSF-61 (pair)	two-way in-ceiling/ in-wall	6.5" (16.51 cm) polypropylene cone	0.75" (1.91 cm) Pivoting PEI	5 - 80 watts	50Hz - 20kHz	88dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	3.49" (8.86 cm)
RSF-62 (pair)	two-way in-ceiling/ in-wall	6.5" (16.51 cm) polypropylene cone	1" (2.54 cm) Pivoting silk	5 - 90 watts	50Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	3.49" (8.86 cm)
RSF-63 (pair)	two-way in-ceiling/ in-wall	6.5" (16.51 cm) IMPP ribbed cone	1" (2.54 cm) Pivoting silk	5 - 100 watts	40Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	3.53" (8.97 cm)
RSF-64 (pair)	two-way in-ceiling/ in-wall	6.5" (16.51 cm) Kevlar cone	1" (2.54 cm) Pivoting Teteron	5 - 120 watts	40Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" dia. (23.19 cm)	8.375" dia. (21.27 cm)	3.69" (9.37 cm)
RSF-61T (each)	in-ceiling single point stereo	6.5" (16.51 cm) IMPP ribbed cone	2 x 0.75" (1.91 cm) silk	5 - 120 watts	40Hz - 20kHz	90dB @ 1w/1m	8 ohms	9.13" día. (23.19 cm)	8.375" dia. (21.27 cm)	3.69" (9.37 cm)

Magnetic grilles:





RSG-S (Sold separately)

5 Forbes Road Newmarket, NH 03857 1.800.638.8055 www.russound.com



CUSTOM WIRELESS SOLUTIONS

There's wireless. And then there's whole house wireless for professional installers. A true wireless solution is more than just a streamer. Real wireless for the custom market takes all of the expected features and adds new dimensions of control and audio integrity. Packaged in a series of interconnectable devices worthy of the audio everywhere label. Now that's XStreamTM.

