



## Standard (Raised) Expanded Metal



Style	Weight (lbs.) Per Sq. Ft.	Opening SWO	Size LWO	Open Area %	Strand Width	Strand Thickness	Overall Thickness
1/2 No. 20	0.43	0.438	0.938	80	0.072	0.036	0.14
1/2 No. 18	0.70	0.438	0.938	72	0.088	0.048	0.172
1/2 No. 16	0.86	0.375	0.938	65	0.087	0.06	0.175
1/2 No. 13	1.47	0.312	0.938	57	0.096	0.09	0.204
3/4 No. 16	0.54	0.813	1.75	78	0.101	0.06	0.21
3/4 No. 13	0.80	0.750	1.688	76	0.096	0.09	0.205
3/4 No. 10	1.20	0.750	1.625	72	0.144	0.09	0.29
3/4 No. 9	1.80	0.688	1.562	68	0.15	0.135	0.312
1 No. 16	0.47	0.938	2	82	0.087	0.06	0.192
1 1/2 No. 16	0.40	1.250	2.625	85	0.108	0.06	0.23
1 1/2 No. 13	0.60	1.888	2.5	85	0.105	0.09	0.242
1 1/2 No. 9	1.20	1.125	2.375	76	0.144	0.135	0.312
1 1/2 No. 6	2.50	1.110	2.313	69	0.203	0.198	0.433



## Flattened Expanded Metal

Style	Weight (lbs.) Per Sq. Ft.	Opening SWO	Size LWO	Open Area %	Strand Width	Strand Thickness
1/2 No. 18	0.66	0.312	1	60	0.097	0.039
1/2 No. 16	0.82	0.312	1	63	0.096	0.056
1/2 No. 13	1.40	0.312	1	52	0.107	0.07
3/4 No. 16	0.51	0.750	1.75	74	0.111	0.048
3/4 No. 13	0.75	0.688	1.781	74	0.106	0.07
3/4 No. 10	1.14	0.637	1.755	68	0.16	0.07
3/4 No. 9	1.71	0.563	1.688	63	0.165	0.12