


# Aerial Work Platforms

## DPL™ Super Series™

### Specifications



Models	DPL-25S		DPL-30S		DPL-35S	
Measurements	US	Metric	US	Metric	US	Metric
Working height*	31 ft 4 in	9.7 m	36 ft	11.14 m	40 ft 10 in	12.62 m
Platform height	25 ft 4 in	7.70 m	30 ft	9.14 m	34 ft 10 in	10.62 m
Height - stowed	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Length - stowed	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m
Width	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m

### Productivity

Lift capacity:	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
Outrigger footprint:						
<b>A</b> length	7 ft 2 in	2.11 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m
<b>B</b> width	4 ft 8.5 in	1.44 m	5 ft 8 in	1.73 m	5 ft 8 in	1.73 m
<b>C</b> corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m
<b>D</b> wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m
<b>E</b> wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
Platform length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform width	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m

### Power

Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V, 190AH Battery

### Weight\*\*

ANSI/CSA (AC)	1,371 lbs	622 kg	1,474 lbs	669 kg	1,574 lbs	714 kg
ANSI/CSA (DC)	1,481 lbs	672 kg	1,584 lbs	718 kg	1,684 lbs	764 kg

### Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
\*\* Weight will vary depending on options and/or country standards

### Features

#### Standard Features

##### Measurements

###### DPL-25S

- 31 ft 4 in (9.7 m) working height
- 25 ft 4 in (7.7 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

###### DPL-30S

- 36 ft (10.97 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

###### DPL-35S

- 40 ft 10 in (12.62 m) working height
- 34 ft 10 in (10.62 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 600 lbs (272 kg) lift capacity

##### Productivity

- Large platform with room for 2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights indicate outrigger installation
- Winch attachment points
- Locking key switch

##### Power

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage

#### Options & Accessories

##### Productivity

- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

##### Platform

- 6ft x 2ft 3in (1.83 m x .69 m)

##### Power

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery



#### Genie United States

6464 185th Ave. NE  
Redmond, WA 98052  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

#### Distributed By:

Effective Date: January, 2017. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2017 Terex Corporation.