



www.tri-flo.com
info@tri-flo.com
+1.303.532.2494

ERADI-FLO 5000-I

Get the Job Done with This 240 Volt 5,000 Watt Industrial Electric Heater

This industrial electric heater is ideal for **killing bed bugs**, drying out moisture, curing paint, warming a construction site, etc.

Features 5,000 watts, this heater requires two 240-volt 13-amp circuits for power.

Lightweight, easy to transport, and features a max temperature of 68°C.

Looking for an easy-to-transport industrial electric heater? The ER5000-I heater is enough to get the job done. Ideal for **bed bug eradication**, various commercial and industrial applications, from construction site heating to restoration, the ER5000-I is as unique as it is versatile. Capable of utilizing the power right on site, this electric heater reaches a maximum temperature of 68°C and produces upwards of 17,100 BTUs.

Specifications:

- 5,000 watt heater
- Compatible with all 240-volt international plugs
- Requires two 240V 13-amp circuits
- Each circuit draws 10.4 amps at 240-volts
- 17,100 BTU's
- Fan speed 800 CFM
- Maximum temperature: 68°C
- Dimensions: 559 mm x 565 mm x 400 mm
- Weight: 15 kg
- CE Mark
- 2-Year Warranty



AC Input Modules



Note: Room size and insulation quality will determine the number of ER5000-I heaters required to successfully eradicate bed bugs.





[Erad-Flo 5000-I 6-19 2](#)



Colorado Tri-Flo Systems, LLC manufactures the Eradi-Flo line of bed bug heaters in Longmont, Colorado USA. Call us to learn more about how we can solve your bed bug issues and drying applications, save money, and make you more profitable with our proactive solutions.

Eradi-Flo heaters are safe, effective, environmentally friendly, and bear the CE Mark. Using airflow technology our heaters deliver the heated airflow necessary to kill bed bugs and other drying applications.

Features	Benefits
Metal construction	Durability for commercial use
Dual airflow ports	Doubles the output flow of heated air
Electric heat	Cheaper and safer than propane and kerosene
Maintains low humidity	Provides dry heat
Uses any international 240-volt plug	Runs using the power source on site
Only one outlet (circuit) required per heater	Put the heater where you need it
Portable and easy to move	Your customers can use it

Eradi-Flo Specifications								
Model	Plug Type	Rated Voltage (Vac)	Rated Current (Aac)	Nominal Heat Generated BTU/hr	Fan CFM*	Maximum Temp	Dimensions	Weight
ER1800-I	All Intl. plugs 	240	7.5 amps	6,150	200	68°C	394mm x 406mm x 260mm	7.3 kg
ER5000-I	All Intl. plugs 	240	20.8 amps 10.4 amps each circuit	17,100	800	68°C	560mm x 566mm x 400mm	15 kg

* Fan volumetric flow reduced at 50Hz by 5% to 20% depending on model and operating conditions

